

HELIOS W7e Integrated Touch Screen Thin Client

Wall or Cart Mountable Touch Screen Kiosk

The HELIOS-W7e touch screen Thin Client is designed for use in Citrix, Terminal Server and Desktop virtualization environments. The local Internet Explorer can be used to run browser based Healthcare applications.

The device is highly energy efficient running on below 30 Watts of power and runs off Intel's power optimized embedded class chipset. Systems are also easily managed remotely using **Thinlabs Device Manager**.

With no moving parts (fan less design), no cables to manage, no mounting headaches, the HELIOS-W7e is an ideal thin client at an excellent price!



integrated, energy efficient solutions for your business needs

KEY FEATURES

- CENTRAL MANAGEMENT USING THINLABS DEVICE MANAGER
- TOUCH SCREEN DRIVEN
- WRITE PROTECTED FILE SYSTEM
- ALLOWS AUTOMATIC LOGIN
- REMOTE CONTROL
- REMOTE SHADOWING
- BUILT-IN DOCUMENT VIEWERS
- 17", 19" WXGA OR 22" WXGA DISPLAY
- LOW ENERGY CONSUMPTION
- POWER OVER ETHERNET SUPPORT (POE+ STANDARD)
- WALL MOUNT SUPPORT
75 / 100 MM VESA STANDARD
- OPTIONAL INTERNAL INTEL BLUETOOTH 4.0 / WI-FI A/B/G/N/AC DUAL BAND COMBO

SOFTWARE

- Windows Embedded Standard 7
- Latest Citrix XenApp client
- Latest VMWARE View Client
- Latest RDP Client
- Internet Explorer 8 with popular plug-ins
- Sun JRE
- Microsoft .net Framework
- Windows Media Player 11
- Large On-screen Keyboard
- Enhanced Write Filter Manager

EXTERNAL PORTS

- Gigabit Ethernet - RJ45
- PS/2 Keyboard & Mouse
- Up to Six USB 2.0
- VGA port
- One RS-232C, second RS-232C optional (powered)
- Parallel Port (optional)
- DC Power in

GRAPHICS

- 17": Up to 1280 x 1024 with resistive touch screen
- 19" WXGA: Up to 1366 x 768 with resistive touch screen
- 22" WXGA: Up to 1920 x 1080 with auto calibrated optical multi touch screen
- 32-bit color
- Integrated 3D graphics engine
- Resistive / Optical Touch Screen

HARDWARE

- 1.6 / 1.86 GHz Dual Core Intel Processor
- 2 / 4 GB DDR3 Memory
- Flash Medium 8 GB SATA DOM (optional 64 GB Solid State Drive)
- 10/100/1000 auto sensing Megabit Ethernet

POWER


- Power – 12V, 5A DC
- **Optional PoE 802.3AT+ support** available on 19" and 22" models

AUDIO SUPPORT

- Intel High Definition Audio Codec
- Headphone / external speaker out and microphone in

REGULATORY/ENVIRONMENTAL COMPLIANCE

- CE / FCC B / EN60950 / RoHS
- Operating: 41°F to 95°F
- Storage : -10°F to 140°F
- 90% max, non-condensing convection cooling - Fanless design
- Energy saving support



CUSTOM SOLUTIONS

Get in touch with us to discuss your options with custom hardware and software specifications.



ONLINE ACCESS

Check out our product portfolio at thinlabs.com

Customer service is our #1 priority. Check out support.thinlabs.com for our dedicated customer service portal.



CORPORATE OFFICE

225 Lincoln Hwy., Suite 178
Fairless Hills, PA 19030
Phone: (215) 269-3339
thinlabs.com

EMEA

86-90 Paul Street
London, EC2A 4NE
ENGLAND
Phone: +44 (0) 20 3322 6050
www.thinlabs.co.uk

E. & O. E.



FOCUSED. CUSTOMER DRIVEN. BEST IN CLASS

